

Inova OnTime® 4-Digit Clock Specifications



Specifications

LED Color Options	Red, Green
Weight	Aluminum cabinet: 2 lbs (0.9 kg); stainless cabinet: 3.75 lbs (1.7 kg); plastic cabinet: 1.6 lbs (0.7 kg)
Cabinet Dimensions	12" L x 6" H x 2.2" D
Display	4" hour and minute numerals
Accuracy	+/- approximately 200 milliseconds
Operating Temperature	32° to 104° F (0° to 40° C)
Operating Humidity	95% maximum, non-condensing
Mounting Options	Surface, Pendant, Cantilever, Flush Inset, Double Sided
Certifications	UL 1950, ETL Listed, CE Marked, RoHS Compliant


Note: Specifications and design are subject to change without notice.

Plastic Cabinet Colors

Black
Pantone 426 C



Putty
Pantone 7500 U



Off-White

Pantone Gray
2 C



Features

- Red or green LED seven-segment display
- Visible from over 150 feet (50 meters)
- Set automatically by SNTP (Simple Network Time Protocol)
- 10/100BaseT Ethernet compatible
- DHCP or static IP addressable
- Power over Ethernet (IEEE 802.3af) technology
- No master clock or serial connection required
- Easily upload firmware upgrades
- Service light status indicator
- Two-year limited warranty
- Telnet control for:
 - IP address configuration
 - SNTP server address
 - Time zone offset from UTC, Daylight Saving Time
 - 12/24 hour format time display
 - Status reporting

Models

Model #	Orientation/Mounting	Cabinet Material	Cabinet Color	# of Digits	LED color
ONT4BK-P	Single-sided	Plastic	Black	4-digit	Red
ONT4PT-P	Single-sided	Plastic	Putty	4-digit	Red
ONT4OW-P	Single-sided	Plastic	Off-white	4-digit	Red
ONT4BK	Single-sided	Aluminum	Black	4-digit	Red
ONT4SS	Single-sided	Stainless Steel	Stainless Steel	4-digit	Red
ONT4FM	Single-sided, flush mount	Plastic case, aluminum face plate	Black	4-digit	Red
ONT4BKFMS	Single-sided, flush mount	Plastic case, stainless face plate	Black and stainless	4-digit	Red
ONT4BK-P-G	Single-sided	Plastic	Black	4-digit	Green
ONT4PT-P-G	Single-sided	Plastic	Putty	4-digit	Green
ONT4OW-P-G	Single-sided	Plastic	Off-white	4-digit	Green
ONT4BK-G	Single-sided	Aluminum	Black	4-digit	Green
ONT4SS-G	Single-sided	Stainless Steel	Stainless Steel	4-digit	Green
ONT4FM-G	Single-sided, flush mount	Plastic case, aluminum face plate	Black	4-digit	Green
ONT4BKFMS-G	Single-sided, flush mount	Plastic case, stainless face plate	Black and stainless	4-digit	Green
ONT4DSBK-P	Double-sided	Plastic	Black	4-digit	Red
ONT4DSPT-P	Double-sided	Plastic	Putty	4-digit	Red
ONT4DSOW-P	Double-sided	Plastic	Off-white	4-digit	Red
ONT4DSBK	Double-sided	Aluminum	Black	4-digit	Red
ONT4DSSS	Double-sided	Stainless Steel	Stainless Steel	4-digit	Red
ONT4DSBK-P-G	Double-sided	Plastic	Black	4-digit	Green
ONT4DSPT-P-G	Double-sided	Plastic	Putty	4-digit	Green
ONT4DSOW-P-G	Double-sided	Plastic	Off-white	4-digit	Green
ONT4DSBK-G	Double-sided	Aluminum	Black	4-digit	Green
ONT4DSSS-G	Double-sided	Stainless Steel	Stainless Steel	4-digit	Green

Accessories

Model #	Description
ONT4KIT	Ethernet mounting kit, 4-digit
ONT4NEMA	NEMA enclosure for 4-digit clock
722442	Power injector, Ethernet, Phihong

Distributed in Australia by

DEXANA
Synchronised Time Solutions

1300 88 44 51
www.dexana.com.au

Dexana Pty Ltd
PO Box 37
Dulwich Hill NSW 2203