

Inova OnTime® 6-Digit Clock Specifications



Specifications

LED Color Options	Red, Green
Weight	Aluminum cabinet: 2.5 lbs (1.1 kg); Stainless Cabinet: 5 lbs (2.3 kg)
Cabinet Dimensions	17.5" L x 6" H x 2.2" D
Display	4" hour and minute numerals; 3" second numerals
Accuracy	+/- approximately 200 milliseconds
Operating Temperature	32° to 104°F (0° to 40°C)
Operating Humidity	95% maximum, non-condensing
Mounting Options	Surface, Pendant, Cantilever, Flush Inset, Double-sided
Certifications	UL 1950, ETL Listed, CE Marked, RoHS Compliant

Note: Specifications and design are subject to change without notice.

Features

- Red or green LED seven-segment display
- Visible from over 150 feet (50 meters)
- Set automatically by SNTP (Simple Network Time Protocol)
- 10/100BaseT Ethernet compatible
- DHCP or static IP addressable
- Power over Ethernet (IEEE 802.3af) technology
- No master clock or serial connection required
- Easily upload firmware upgrades
- Service light status indicator
- Two-year limited warranty
- Telnet control for:
 - IP address configuration
 - SNTP server address
 - Time zone offset from UTC, Daylight Saving Time
 - 12/24 hour format time display
 - Status reporting

Models

Model #	Orientation/Mounting	Cabinet Material	Cabinet Color	# of Digits	LED color
ONT6BK	Single-sided	Aluminum	Black	6-digit	Red
ONT6SS	Single-sided	Stainless Steel	Stainless	6-digit	Red
ONT6FM	Single-sided; flush mount	Aluminum	Black	6-digit	Red
ONT6BKFMS	Single-sided; flush mount	Black aluminum case; Stainless face plate	Black and stainless	6-digit	Red
ONT6BK-G	Single-sided	Aluminum	Black	6-digit	Green
ONT6SS-G	Single-sided	Stainless Steel	Stainless Steel	6-digit	Green
ONT6FM-G	Single-sided; flush mount	Aluminum	Black	6-digit	Green
ONT6BKFMS-G	Single-sided; flush mount	Black aluminum case; Stainless face plate	Black and stainless	6-digit	Green
ONT6DSBK	Double-sided	Aluminum	Black	6-digit	Red
ONT6DSSS	Double-sided	Stainless Steel	Stainless Steel	6-digit	Red
ONT6DSBK-G	Double-sided	Aluminum	Black	6-digit	Green
ONT6DSSS-G	Double-sided	Stainless Steel	Stainless Steel	6-digit	Green

Accessories

Model #	Description
ONT6KIT	Ethernet mounting kit, 6-digit
ONT6NEMA	NEMA enclosure for 6-digit clock
722442	Power injector, Ethernet, Pihong

Distributed in Australia by

DEXANA
Synchronised Time Solutions

1300 88 44 51
www.dexana.com.au

Dexana Pty Ltd
PO Box 37
Dulwich Hill NSW 2203